



TECHNICAL DATA SHEET 410016

Room 9,11 Floor, Chuangxin Building Block 1#, No.1, Technology Road, Technology Chuangxin Park, West of Dayabay, Huizhou City, Guangdong, P.R. China
Tel.: 0752-5533798 Fax.: 0752-5533798-811

DESCRIPTION:

Tacusil™ 410016 is a black cyanoacrylate adhesive which has been developed for all applications under thermal and/or climatic conditions. The product shows excellent resistance against dynamic loads like impacts or vibrations. Due to its short-term temperature resistance up to 140 °C, it is also suitable for SMD technique, where later soldering bath is requested.

The black color allows the use in loudspeaker application, too.

TYPICAL PROPERTIES: All properties given are at 23 °C unless otherwise noted.

Property:	Value:	Unit:
Chemical Base	Cyanoacrylicacid-ethylester	
Color	Black	
Viscosity		
Brookfield-RVT, 25°C, spindle 3 @100U/min	300~500	mPas
Cone-plate-system, 25°C Shear rate 1000S ⁻¹	80~180	mPas
Density	1.06	g/cm ³
Hardness	65-75	Shore D
Flashpoint	87	°C
Thermal Range	-55 to 120	°C
Fixture Time on:		
Aluminum /Aluminum	25~45	seconds
NBR/NBR	<25	seconds
Neoprene/Neoprene	<25	seconds
Final strength	24	hours
Tensile Shear Strength on:		
Steel/Steel	>20	N/mm ²
Shelf life @ room temperature	9	months

Tacusil™ MAKES NO EXPRESS OR IMPLIED WARRANTIES OR MERCHANTABILITY, FITNESS OR OTHERWISE with respect to its products. In addition, while the information contained herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestions for use are made without guarantee inasmuch as conditions of use are beyond our control. The properties given are typical values and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.