



Room 9,11 Floor, Chuangxin Building Block 1, No.1, Technology Road, Technology Chuangxin Park,, West of Dayabay, Huizhou City, Guangdong, P.R. China TEL (86 752) 5533798 FAX (86 752) 5533798-811

Description:

Tacusil[™] S20003 is a general purpose paint and gasket remover. Its special formulation clings to surface's and penetrates to lift off and strip a range of gasket materials in addition to paint, varnish, shellac, decals and adhesives

Features:

- Foam Penetrating action easily lift up gasket paint and other coatings
- ♦ Non corrosive contains no acid that would attack steel, aluminum and other surfaces
- ♦ Efficient thick coatings can be removed in one application
- ♦ Easy application simply spray onto the surface and allow it to react
- ♦ General Purpose Use for a wide range of materials and coatings

Specifications:

Viscosity	100-140 cps
Approvals	MIL-R-25134B

User Guide:

- ♦ Not recommended for linoleum, fiberglass, plastic or other synthetic materials.
- Spray S20003 10-15 cm from the substrate surface, soak for several minutes. When the paint/ coating starts to peel and peel off, rinse with a high pressure water gun. To re-paint, first clean the surface with solvent.
- ♦ When removing epoxy, polyester or urethane coating, use the product several times and prolong the soaking time.

TACUSIL[™] MAKES NO EXPRESS OR IMPLIED WARRANTIES OR MERCHANTABILITY, FITNESS OR OTHERWISE with respect to its products. In addition, while the information contained herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestions for use are made without guarantee inasmuch as conditions of use are beyond our control. The properties given are typical values and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes. Page 1 of 1